




## 6 Conductor Solid CL2R Rated Thermostat Cable



### Applications

Vericom 6 conductor solid CL2R rated thermostat cable supports in-wall use and certain low-voltage applications. This cable is ideal for class 2 remote-control, signaling, and power-limited circuits and is suitable for in-wall installation in multi-story commercial building or residential environments.

### Description / Specifications

This 6 conductor solid CL2R rated thermostat cable is offered in 18 AWG and is composed of 6 wires (Red, White, Green, Blue, Yellow, Brown) inside an In-Wall Riser rated jacket. This cable is approved for 150 volts and has a temperature range of -20°C to 60°C. Our thermostat cables are CMR and CL2R and meet UL 1685 Vertical Tray, which are perfect for commercial installation in vertical floor-to-floor runs, where the length exceeds one story.

### Features & Benefits

- CL2R rated jacket for in-wall residential or commercial installations in vertical floor-to-floor runs, where the length exceeds one story
- UL Listed and RoHS compliant to ensure safety requirements are met
- Offered in 18 AWG solid copper conductor to suit your specific application
- Spool packaging to ease installation and storage

### Standards Compliance

- UL 1685 Vertical Tray and UL 1666
- UL Standard 13, Power Limited Circuit Cable
- UL Listed Type CL2R and CMR
- NEC Article 725
- RoHS Compliant



## 6 Conductor Solid CL2R Rated Thermostat Cable

### Ordering Information

Description				
Item No.	Conductor	Packaging	Cable Weight	Color
<b>6 Conductor Solid Riser Rated Thermostat Cable</b>				
HT186-02549	18 AWG	250 ft Spool	9 lb / 250 ft	White

### Cable Marking

VERICOM E364604 **XX** AWG 6C 60 °C (UL) TYPE CL2R ---  
CMR SUNLIGHT RESISTANT

For accurate cable marking, replace the **XX** with the appropriate wire gauge.

### 18 AWG Construction

**Conductor Material:** 18 AWG 5C Solid Bare Copper  
**Conductor Diameter:** 0.040 in. (1.024 mm)  
**Insulation Material:** Polypropylene (PP)  
**Insulation Thickness:** 0.008 in. (0.203 mm)  
**Insulation Diameter:** 0.057 in. (1.45 mm)  
**Insulation Color Code:** Red, White, Green, Blue, Yellow, Brown

**Ripcord:** Nylon  
**Jacket Material:** Sunlight Resistant Polyvinyl Chloride (SRPVC)  
**Jacket Thickness:** 0.016 in. (0.41 mm)  
**Jacket Color:** Specified By Item Number  
**Jacket Diameter:** 0.197 in. (5.00 mm)

### Electrical

**Nominal Mutual Capacitance:** 25 Pf/m  
**Nominal Conductor DC Resistance (DCR@20°C):** 6.5 Ω/1000 ft

**Voltage Rating:** 150V

### Environmental Conditions

**Operating Temperature:** -4 °F to 140 °F (-20 °C to 60 °C)