



PACKING

1 PC IN A ZIP BAG



***Note: All relevant materials are complied with RoHS directive.**

9	TRANSPARENT COIL CABLE TIE, LENGTH 40mm	1
8	L/N WITH TRANSPARENT LABEL 20*20mm	1
7	BLACK HEAT SHRINK TUBE Ø4.0*15mm	2
6	MARK RING, COLOR YELLOW (#1 & #2)	4
5	SC/UPC MM/ IVORY HOUSING / BOOT COLOR: RED & BLACK	1 SET
4	LC/UPC MM/ AQUA HOUSING / BOOT COLOR: AQUA TUBE COLOR: YELLOW & WHITE	1 SET
3	MM, DX/ UL, OM3, 10G, 50/ 125 OD1.8*3.7mm, CORNING, JACKET AQUA (PT3115C), DRAWING NO. EQ00602C-020	L + 100mm
2	SC/UPC MM/ 4.0	2
1	LC/UPC MM/ 4.0	2
No.	COMPONENT DESCRIPTION	Quantity

CABLE MARKING

VERICOM OPTICAL FIBER CABLE (UL) E519838 TYPE OFNR 70°C RISER CABLE 1.8mm OM3 TIA-568-C.3 ROHS COMPLIANT BATCH NO XXM

P1		P2
1	_____	1
2	_____	2

APPROVED			UNLESS OTHERWISE SPECIFIED: TOLERANCES 0 ~ 200 mm ± 10 mm 201 ~ 1000 mm ± 20 mm 1001 ~ 1500 mm ± 25 mm 1501 ~ 2100 mm ± 30 mm 2100 ↑ ± 40 mm
CHECKED			
DRAWING		TITLE	OPTICAL FIBER CABLE
DATE	06/14/20	ITEM NO.	PC06U30218RAQ**M
CHECKED		UNIT: mm	

Length (L)	Bag	Quantity
1M	150*240*0.08mm	400
2M	150*240*0.08mm	300
3M	150*240*0.08mm	250
4M	150*240*0.08mm	200
5M	150*240*0.08mm	200
6M	150*240*0.08mm	160
7M	150*240*0.08mm	140
8M	150*240*0.08mm	130
9M	150*240*0.08mm	130
10M	150*240*0.08mm	120
11M	170*290*0.08mm	120
12M	170*290*0.08mm	110
13M	170*290*0.08mm	100
14M	170*290*0.08mm	80
15M	170*290*0.08mm	70
20M	170*290*0.08mm	60
25M	170*290*0.08mm	50
30M	170*290*0.08mm	40

TRANSMISSION PERFORMANCE

Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-10 (FOCIS-10), TIA-604-3 (FOCIS-3)

MECHANICAL

Connector Insertion Loss : 0.25dB max. (LC and SC Multimode - Standard IL)

Connector Return Loss : 26dB min. (OM3 and OM4)

Connector Durability : 500 Cycles


PHYSICAL

Storage and shipping temperature: -40°C to 70°C

Operating and installation temperature: -20°C to 70°C

NOTE:

All relevant materials are RoHS Compliant.

APPROVED			UNLESS OTHERWISE SPECIFIED: TOLERANCES		
CHECKED			0 ~ 200 mm	± 10 mm	
DRAWING		TITLE	OPTICAL FIBER CABLE	201 ~ 1000 mm	± 20 mm
DATE	06/14/20	ITEM NO.	PC06U30218RAQ**M	1001 ~ 1500 mm	± 25 mm
		CHECKED		1501 ~ 2100 mm	± 30 mm
				2100 ↑	± 40 mm
				UNIT: mm	