



PACKING

1 PC IN A ZIP BAG



CABLE MARKING

VERICOM OPTICAL FIBER CABLE (UL) E519838 TYPE OFNR 70°C RISER CABLE 1.8mm OS1/OS2 TIA-568-C.3 ROHS COMPLIANT BATCH NO XXM

| | |
|-----------|-----------|
| P1 | P2 |
| 1 | 1 |

***Note: All relevant materials are complied with RoHS directive.**

| | | | |
|----------|---|--|---------------------|
| 5 | TRANSPARENT COIL CABLE TIE, LENGTH 40mm | 1 | |
| 4 | L/N WITH TRANSPARENT LABEL 20*20mm | 1 | |
| 3 | LC/APC SM/ HOUSING COLOR: GREEN / BOOT COLOR: GREEN TUBE COLOR: YELLOW | 2 SET | |
| 2 | SM, SX/ UL, G652D, OD1.8 mm, OFNR, CORNING, JACKET YELLOW (PT123C), DRAWING NO. EQ00601C-023 | L + 100mm | |
| 1 | LC/UPC SM/ 1.0 | 2 | |
| No. | COMPONENT DESCRIPTION | Quantity | |
| APPROVED | | UNLESS OTHERWISE SPECIFIED: TOLERANCES 0 ~ 200 mm ± 10 mm 201 ~ 1000 mm ± 20 mm 1001 ~ 1500 mm ± 25 mm 1501 ~ 2100 mm ± 30 mm 2100 ↑ ± 40 mm | |
| CHECKED | | | |
| DRAWING | TITLE | | OPTICAL FIBER CABLE |
| DATE | ITEM NO. | | PC2A2A1118RYE**M |
| CHECKED | | UNIT: mm | |

| Length (L) | Bag | Quantity |
|------------|----------------|----------|
| 1M | 150*240*0.08mm | 450 |
| 2M | 150*240*0.08mm | 350 |
| 3M | 150*240*0.08mm | 300 |
| 4M | 150*240*0.08mm | 300 |
| 5M | 150*240*0.08mm | 250 |
| 6M | 150*240*0.08mm | 250 |
| 7M | 150*240*0.08mm | 200 |
| 8M | 150*240*0.08mm | 200 |
| 9M | 150*240*0.08mm | 150 |
| 10M | 150*240*0.08mm | 150 |

TRANSMISSION PERFORMANCE

Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3,
TIA-604-10 (FOCIS-10)

MECHANICAL

Connector Insertion Loss : 0.30dB max.

Connector Return Loss : 65dB min.

Connector Durability : 500 Cycles



PHYSICAL

Storage and shipping temperature: -40°C to 70°C

Operating and installation temperature: -20°C to 70°C

NOTE:

All relevant materials are RoHS Compliant.

| | | | | | |
|----------|----------|---|---------------------|--|--|
| APPROVED | |  | | UNLESS OTHERWISE SPECIFIED: TOLERANCES 0 ~ 200 mm ± 10 mm 201 ~ 1000 mm ± 20 mm 1001 ~ 1500 mm ± 25 mm 1501 ~ 2100 mm ± 30 mm 2100 ↑ ± 40 mm | |
| CHECKED | | | | | |
| DRAWING | | TITLE | OPTICAL FIBER CABLE | | |
| DATE | 03/02/21 | ITEM NO. | PC2A2A1118RYE**M | | UNIT: mm  |

CHECKED