



## RG6 Universal Compression Connector





### Applications

The Vericom 75 ohm RG6 compression connectors are manufactured to meet the demands and expectations of antenna, cable television and satellite television installations. In addition to being suitable for indoor applications, these compression connectors are SCTE tested and weatherproof for hostile outdoor environments.

### Description / Specifications

This RG6 compression connectors is made from a patented single piece universal design that fits any dual-shield, tri-shield or quad-shield RG6 coaxial cable and works with any standard compression tool.

### Related Products

<p><b>RG6 CM Dual-Shield CCS Coax Cable</b></p>  <p>Item # XRG06-01503 (Black, Spool) Item # XRG06-01504 (White, Spool)</p> <p>Item# XRG06-02404 (Black, Reel-In-Box) Item# XRG06-02405 (White, Reel-In-Box)</p>	<p><b>Ratcheting Coax Compression Tool</b></p>  <p>Item No. WTCXP-03630</p>
--	--

### Features & Benefits

- Universal design fits any dual-shield, tri-shield or quad shield RG6 coaxial cable with any standard compression tool
- High performance F-type connector capable of a bandwidth of up to 3 GHz
- Precision machined body with mil spec plating
- Compression sleeve locks coax cable securely and positively in place
- Weatherproof for hostile outdoor environments
- Bulk packaged in bags of 50

### Standards Compliance & Certifications

- SCTE Compliant
- HughesNet® Approved
- SCTE-103-2004 (*DC Contact Resistance*)
- ASTM-B117-03 (*Salt Spray Test*)
- ANSI/SCTE-99-2004 (*Axial Pull Test*)
- SCTE-98-2004 (*Tightening Torque*)
- SCTE-73-2002 (*Coaxial Insertion Force*)
- SCTE-48-3-2004 (*Shielding Effectiveness*)
- ANSI/SCTE-04-1997 (*F Connector Return Loss*)
- SBCA Standards of Physical Dimension Tolerance
- GR-1503-Core, Issue 1, March 1995 UV Degradation

### Electrical & Mechanical

**Impedance:** 75Ω  
**Bandwidth:** 0-3 GHz  
**Shielding Effectiveness:** > 90dB

### Environmental Conditions

**Operating Temperature:** -40 °F to 140 °F (-10 °C to 60 °C)

### Ordering Information

Description	
Universal Compression Connector for RG6 Coax Cable	
Item No.	Packaging
PV1666	Bulk (50 Per Bag)

TECHNICAL SHEETS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

REV.20230804.4