



## 12VDC Power Supply Wall 100-240 VAC



### Features & Benefits

- Compact size
  - Low power consumption
- Meets the U.S. Department of energy standards for Level VI efficiency
- Suitable for use in the United States

### Standards Compliance

- c(UL)us Listed
- RoHS
- FCC
- Efficiency VI Standard

### Applications

Vericom power adapters are designed to work with a variety of electronic devices, including modems, converters, eMTA, gateways, routers and set-top boxes.

### Description / Specifications

Our power adapters are designed to meet a number of critical parameters, including those for input voltage, output voltage, output power, output connector size and for specific types of adapter use. These adapters are UL Listed, and are tested for performance and reliability. Our adapters are designed to meet the specific requirements of the devices being powered, are output short-circuit protected and are built for maximum longevity.

### Ordering Information

Description	Input Voltage	Output Voltage
Power Supply - Wall	100-240 VAC	12 VDC
Item No.	Output Current	Pin Size
XPSAD-04837	1.0 AMPS	2.5 ID / 5.5 OD
XPSAD-11335	1.25 AMPS	MLX Connector
XPSAD-04838	1.5 AMPS	2.1 ID / 5.5 OD
XPSAD-05542	1.5 AMPS	2.5 ID / 5.5 OD
XPSAD-05543	1.5 AMPS	3.0 ID / 6.5 OD
XPSAD-04840	2.0 AMPS	2.1 ID / 5.5 OD
XPSAD-11331	2.0 AMPS	2.5 ID / 5.5 OD
XPSAD-05544	2.5 AMPS	2.1 ID / 5.5 OD
XPSAD-04842	2.5 AMPS	2.5 ID / 5.5 OD
XPSAD-05545	3.0 AMPS	1.3 ID / 3.8 OD
XPSAD-05546	3.0 AMPS	2.1 ID / 5.5 OD
XPSAD-05110	3.0 AMPS	2.5 ID / 5.5 OD
XPSAD-05303	3.5 AMPS	2.1 ID / 5.5 OD
XPSAD-11393	3.5 AMPS	2.5 ID / 5.5 OD
XPSAD-05331	4.0 AMPS	2.1 ID / 5.5 OD
XPSAD-11394	4.0 AMPS	2.5 ID / 5.5 OD